



High Capacity, High Efficiency Package Air Conditioning

- DRU Series
 - DRU-15600AC

Standard Features:

- 1" double wall Hybralume ™ construction.
- 1" double wall access doors with stain less hinges.
- 11.52 EER
- Compressors and unit controls contained within single isolated compartment.
- Scroll compressors installed on sheet metal deck with rubber isolation mounts for quiet efficient operation.
- Direct drive blower plenum fan with VFD drive.
- Direct drive condenser fan(s).
- Bottom access return and supply air.
- Roof sloped for proper drainage.
- Single point power connection.
- Thermostatic expansion valves on DX coils.
- Automatic reset low pressure cutoffs.
- Test report, wiring diagram, installation manual and startup form in control access compartment.
- Labeled & listed under ETL with UL1995.
- R410A refrigerant
- Low profile

Optional Features:

- Economizer and recovery.
- Power exhaust
- Blower motors may be oversized and/or high efficiency.
- · GFI convenience outlet.
- Smoke detectors or firestats in return and/or supply air.
- Compressor isolation valves.
- Phase and brown-out protection.
- Disconnect switch.
- Burglar bars on return and/or supply air.
- Insulated concentric supply diffuser and return air box.
- Factory structural curb
- NOVAR ETM-3051 compatible.

Resources Available for This Product

• Catalog By Mail





United Metal Products

1920 E Encanto Drive Tempe, AZ 85281 T 480.968.9550 F 480.968.9555 www.unitedmetal.com